

WINCHES - without CABLE

Page 1 of 2

| WINCH - WITH CABLE 1:1 | | | | |
|------------------------|--------|---|--|--|
| PART# | Finish | Australian Made by Winches Down Under 1 Speed - 1:1 Ratio | | |
| WNW-1-ZP | Z/P | Fixed Handle | | |
| WNW-1-BLU | Blue | Rated Capacity: 300 kg Line Pull Recommended cable: 4mm x nom. 5m long c/w S/S 'S' Hook Blue Powder Coated bodies are Zinc Plated first | | |
| | | Load testing meets Australian Standards - AS1418.2 - 1997 Clause 1.11.3 | | |

| WINCH - WITH CABLE 3:1 | | | |
|------------------------|--------|--|--|
| PART# | Finish | Australian Made by Winches Down Under1 Speed - 3:1 Ratio | |
| WNW-3-ZP | Z/P | Fixed Handle | |
| WNW-3-BLU | Blue | Rated Capacity: 500 kg Line Pull Recommended cable: 4mm x nom. 5m long c/w S/S 'S' Hook Blue Powder Coated bodies are Zinc Plated first Load testing meets Australian Standards - AS1418.2 - 1997 Clause 1.11.3 | |

| WINCH - WITH CABLE 3:1/1:1 | | | |
|----------------------------|--------|--|--|
| PART# | Finish | Australian Made by Winches Down Under 2 Speed - 1:1 & 3:1 Ratio | |
| WNW-3/1-ZP | Z/P | Removable Handle | |
| WNW-3/1-BLU | Blue | Rated Capacity: 500 kg Line Pull Recommended cable: 4mm x nom. 5m long c/w S/S 'S' Hook Blue Powder Coated bodies are Zinc Plated first Load testing meets Australian Standards - AS1418.2 - 1997 Clause 1.11.3 | |

| WINCH - WITH CABLE 5:1 | | | |
|------------------------|--------|---|--|
| PART# | Finish | Australian Made by Winches Down Under 1 Speed - 5:1 Ratio | |
| WNW-5-ZP | Z/P | Fixed Handle | |
| WNW-5-BLU | Blue | Rated Capacity: 700 kg Line Pull Recommended cable: 5mm x nom. 6m long c/w Snap Hook Blue Powder Coated bodies are Zinc Plated first Load testing meets Australian Standards - AS1418.2 - 1997 Clause 1.11.3 | |



Page 2 of 2

WINCHES - without CABLE (continued)

| WINCH - WITH CABLE 5:1/1:1 | | | | |
|----------------------------|--------|---|--|--|
| PART# | Finish | Australian Made by Winches Down Under 2 Speed - 1:1 & 5:1 Ratio | | |
| WNW-5/1-ZP | Z/P | Removable Handle | | |
| WNW-5/1-BLU | Blue | Rated Capacity: 700 kg Line Pull Recommended cable: 5mm x nom. 6m long c/w Snap Hook Blue Powder Coated bodies are Zinc Plated first Load testing meets Australian Standards - | | |
| | | Load testing meets Australian Standards - AS1418.2 - 1997 Clause 1.11.3 | | |

| WINCH - WITH CABLE 10:1/5:1/1:1 | | | |
|---------------------------------|--------|---|--|
| PART# | Finish | Australian Made by Winches Down Under 3 Speed - 1:1, 5:1 & 10:1 Ratio | |
| WNW-10/5-ZP | Z/P | Removable Handle | |
| WNW-10/5-BLU | Blue | Rated Capacity: 800 kg Line Pull Recommended cable: 5mm x nom. 8m long c/w | |
| | | Snap Hook Blue Powder Coated bodies are Zinc Plated first Load tosting recent Australian Standards | |
| | | Load testing meets Australian Standards - AS1418.2 - 1997 Clause 1.11.3 | |

OPERATING INSTRUCTIONS

- 1. Ensure that the cable length specified allows a minimum of 3 wraps of cable will remain on the drum at all times (This anchors the cable onto the drum). NEVER fully extend the cable when under load.
- 2. Bushes / bearings should be oiled frequently.
- 3. Do not use as a load restraining device. Restrain load by other means (eg. Safety chain).
- 4. Not designed for lifting applications. (See our range of Brake Winches available for lifting)
- 5. Do not use for the movement of humans.